

APG-2405n

Standards Compliance: IEEE 802.11 n/b/g; IEEE 802.3; IEEE 802.3u; IEEE 802.3p; IEEE802.3x; IEEE 802.3af

SDRAM: 16M Bytes

Flash: 2M Byte

Radio Frequency Type: DSSS / OFDM

Modulation: OFDM: BPSK, QPSK, 16-QAM, 64-QAM, DBPSK, DQPSK, CCK

Frequency Band: America/FCC: 2.412~2.462 GHz (11 channels) Europe CE/ETSI: 2.412~2.472 GHz (13 channels)

Transmission Power: Up to 20dBm

Transmission Rate: IEEE 802.11b: 1/ 2/ 5.5/ 11Mbps IEEE 802.11g: 6/ 9/ 12/ 18/ 24/ 36/ 48/ 54Mbps

Access Point Interfaces: Auto MDI/MDI-X Ethernet 10/100/1000 Base-TX: RJ-45

Sensitivity: IEEE 802.11b: -92dBm @ 1Mbps; -85dBm @ 11Mbps, PER < 8% IEEE 802.11g: -88dBm @ 6Mbps; -73dBm @ 54Mbps, PER <10% IEEE 802.11n: -90dBm@MCS8; -70dBm@MCS15, PER <10%

Antenna Type: 2 printed antennas

Security Systems: 64-bit / 128-bit WEP encryption; Wi-Fi Protected Access (WPA) / WPA2

Wireless Setting: Operation Mode – AP / Repeater / WDS PTP and PTMP

Operating Environment Operating Temperature: 30 ~ +70°C

Power: DC 48 V + 5%; 1.37A(Max); AC adapter 100V ~240V

Network Management System OS Support: Windows 2000/XP/Vista

Regulatory Approval: FCC Part 15 B (US); CE

Warranty: One year limited

STANDARD ACCESSORIES:



<http://www.zerix.com.ph>
inquirenow@zerix.com.ph
Tel. Nos.: (632)348.3749
Fax No.: (932)914.1122

OPTIMUM SOURCE, INC.
2501 The Orient Square, F. Ortigas Jr. Rd.
Ortigas Ctr., Pasig City 1605 Philippines